

Publication number: DE19800653 (A1)

Publication date: 1999-07-15

Inventor(s): HUBER ALBERT M [DE]; HUBER JOACHIM CHR [DE]; HUBER WOLFGANG ALEXANDER [DE] +

Applicant(s): HUBER ALBERT M [DE]; HUBER JOACHIM CHR [DE]; HUBER WOLFGANG ALEXANDER [DE] +

Classification:

- international: **B04B1/00; D21D5/22; B04B1/00; D21D5/00;** (IPC1-7): D21D5/22; B04B1/00; B04B7/08; B04B9/12; B04B11/02; B04B15/06

- European: B04B1/00; D21D5/22

Application number: DE19981000653 19980109

Priority number(s): DE19981000653 19980109

**Also published as:**

EP1056904 (A2)  
WO9935331 (A2)  
WO9935331 (A3)  
CA2317528 (A1)

**Cited documents:**

DE19537567 (A1)  
DE3409068 (A1)  
DE8331079U (U1)  
US3791575 (A)  
WO9200810 (A1)

**View all**

[View INPADOC patent family](#)

[View list of citing documents](#)

[Report a data error here](#)

## Abstract of **DE 19800653 (A1)**

[Translate this text](#)

The invention relates to a solid bowl centrifuge (1) for multiphase mixtures, preferably three-phase mixtures, which is especially meant for fibrous material suspensions used in the paper industry. The solid bowl centrifuge (1) has a housing (2) and a rotor (7) which is provided for separating the multiphase mixture into a light, middle and heavy fraction. At least one orifice (41) situated in the bowl of the rotor (7) is provided for conveying the heavy fraction out. A conveying device (51) is arranged in a chamber (43) between the outer wall (24) of the rotor (7) and the housing (2). Said conveying device conveys a blocking medium into the chamber (43) with at least the pressure prevailing there and in a direction of at least one orifice (41) provided for the heavy fraction.